



OKS 1600 - Product Information

Fields of Application:

Protection of surfaces of all kinds and welding nozzles for oxy-acetylene gas, inert-gas arc welding and arc welding. Prevents baking of weld spatters on surface and welding nozzle.

OKS 1600

Spatter Release, water-based concentrate



Advantages and Benefits:

Excellent suited as reliable transparent parting film. Effectively protects workpiece and welding nozzle against adhering of weld spatters. Later painting over, metallising and printing following prior degreasing easily possible. Environment-friendly, as water-based.

Application:

For best results clean the surfaces, first mechanically and then with OKS 2610/OKS 2611 Universal Cleaner. Dilution with water possible to 1:5. Spray a thin layer evenly to the surface affected by welding spatters. Protect product from freezing. For further questions please contact our Technical Department.

Additional Information:

Packaging (Article number):

- 5 l Canister (01600050)
- 25 l Canister (01600062)

Version:

E-05.1/05

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. ® = Registered Trademark



OKS 1600 Spatter Release, water-based concentrate

Technical Data

	Norm	Conditions	Unit	Value
Base Oil				
Type				Water
Additives				
Additive				Native fatty oil
Application Data				
Dichte	DIN EN ISO 3838	+20°C	g/ml	1,0
Colour				transparent

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. ® = Registered Trademark