




## OKS 2301 - Product Information

### Fields of Application:

Preservation of bare metal surfaces of all kinds, which are unsheltered stored for longer periods and effected to of weathering (industrial atmosphere, tropics, ocean). Protected parts retain their decorative appearance, as no surface discolouration occurs. Ideal on-call and storage protection for spare parts with possibility of direction installation. Can be welded without degreasing. Easily removable before coating (e.g. with OKS 2610/OKS 2611 Universal Cleaner).

### OKS 2301

#### Mould Protector, Spray



### Advantages and Benefits:

Highly effective due to good film-forming properties with lasting water-repelling effect. Excellently suited for producing non-slip dry, greenish protective films. Outstanding corrosion and oxidation protection with lubricating effect. No removal prior to commissioning, as compatible with all lubricants. Waterproof and resistant to weathering. Suitable for all climate zones.

### Application:

For optimum results clean surfaces, first mechanically and then with OKS 2610/OKS 2611 Universal Cleaner. The surfaces must be metallic bright and dry. Shake well before use. Spray from 20 - 30 cm distance to the prepared surface. Local excess should be avoided. Drying conditions acc. to the following technical data. For further questions please contact our technical department.

### Additional Information:

Packaging (Article number):  
- 400 ml Spray (02301004)

Version:  
E-05.1/05

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. ® = Registered Trademark



## OKS 2301 Mould Protector, Spray

### Technical Data

	Norm	Conditions	Unit	Value
<b>Solid Lubricants</b>				
Type				Synthetic wax
<b>Solvents</b>				
Type				Special boiling point gasoline
<b>Additives</b>				
Type				Corrosion protection
<b>Film layer</b>				
Optimum layer thickness	DIN 50 981/50 984	DIN 50 982-2	µm	> 10
Application temperature			°C	Room temperatur
Drying time		at 20°C	h	0,1
Surface coverage			m²/Tin	5
<b>Application Data</b>				
Density	DIN EN ISO 3838	+20°C	g/ml	0,8
Colour				greenish
<b>Service Temperatures</b>				
Minimum service temperature			°C	-40
Maximum service temperature			°C	70
<b>Corrosion Protection Tests</b>				
Salt spray test	DIN 50 021	50 µm	h	> 1.000

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. ® = Registered Trademark