




OKS 469 - Product Information

Fields of Application:

For the lubrication of plastic/plastic and plastic/metal pairs like e.g. one-way tap cocks in the food industry or cup holders in the automotive industry. Silicone free alternative for the lubrication of O-rings and sealings during assembly.


OKS 469 Plastic and Elastomer Lubricant



Advantages and Benefits:

Excellent adhesion on plastics with neutral behavior to plastics and elastomers. Constant characteristics without drying out, hardening or bleeding out. Toxicologically harmless acc. to § 31, chapter 1, of the German Lebensmittel- und Bedarfsgegenständegesetzes. Registered from the NSF in the category H1 under the number 131 380. No interference with the quality, taste and odour of beverages. Good dosability through automated lubrication systems.

Application:



For best results clean the lubrication point carefully, e.g. with OKS 2610/OKS 2611 Universal Cleaner. Apply grease evenly thin with a brush or spatula. Avoid excess. Instructions of the machine and plastic manufacturer have to be observed. Relubrication periods and amount have to be stated according to the service conditions. Only mix with appropriate lubricants. For additional questions please contact our Technical Department.

Additional Information:

Packaging (Article number):

- 1 kg tin (00469034)
- 5 kg hobbock (00469050)
- 25 kg hobbock (00469062)

Date:

E-03.1/06

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. ® = Registered Trademark



OKS 469 Plastic and Elastomer Lubricant

Technical Data

	Norm	Conditions	Measurment	Value
Base Oil				
Type				Polyalfaolefine
Vissosity		+40°C	mm²/s	400
Thickener				
Type				anorganic
Consistency	DIN 51 818	DIN ISO 2137	NLGI- Class	2
Penetration	DIN ISO 2137		0.1 mm	265 - 295
Oil separation	DIN 51 817	168h/40°C	Weight-%	1.36
Application data				
Density	DIN EN ISO 3838	+20°C	g/cm³	0.84
Color				colorless-transparent
Application temperature				
Lower application temperature			°C	-40
Upper application temperature			°C	150
Releases/Specifications				
Food Industry				Meets §31, Chpt. 1, LMBG NSF H1 Reg. Nr. 131 380 Release of the LGA Nürnberg Release of the BPV Weihenstephan

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. ® = Registered Trademark